

# Technical data sheet

## Clamp clip 2056, W-foot, double, metal pressure trough, FT

Item number: 1188344



Clamp clip with W-foot, metal pressure trough with rounded edges to protect the cable. For vertical and horizontal mounting of 2 single cables on angle irons shaft length 40 mm. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. We recommend the use of a counter-trough. In AC circuits the product shall not be used with single core cable in galvanised cable ladders and profile rails because of the inductive heating.



St

Steel

FT

Hot-dip galvanised

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 1188344                  |
| Type                               | BS-W2-M-16 FT            |
| Description 1                      | Clamp clip 2056          |
| Description 2                      | double                   |
| Manufacturer                       | OBO                      |
| Dimension                          | 12-16mm                  |
| Material                           | Steel                    |
| Surface                            | Hot-dip galvanised       |
| Surface standard                   | DIN EN ISO 1461          |
| Smallest sales unit                | 50                       |
| Unit of quantity                   | Piece                    |
| Weight                             | 5.319 kg                 |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,1988 kg CO2e / 1 Piece |


# Technical data sheet

Clamp clip 2056, W-foot, double, metal pressure trough, FT

Item number: 1188344



## Dimensions



|                  |         |
|------------------|---------|
| Length           | 22.5 mm |
| Width            | 20 mm   |
| Height           | 105 mm  |
| Plate thickness  | 1.5 mm  |
| Dimension A      | 22.5 mm |
| Dimension B      | 20 mm   |
| Dimension C      | 28 mm   |
| Dimension G (mm) | M6      |
| Dimension H      | 105 mm  |
| Dimension L      | 46 mm   |
| Dimension t      | 1.5 mm  |

## Technical data

|                               |                |
|-------------------------------|----------------|
| Number of cables/pipes        | 2              |
| For pipe diameter, max.       | 16 mm          |
| For pipe diameter, min.       | 12 mm          |
| Thread                        | M6             |
| Halogen-free                  | yes            |
| Length of external dimensions | 28 mm          |
| Max. Tightening torque        | 3 Nm           |
| With metal trough             | yes            |
| Mounting type                 | Angle profile  |
| Slot width                    | 10 mm          |
| Clamping range D, max.        | 16 mm          |
| Clamping range D, min.        | 12 mm          |
| Surface addition              | hot galvanised |
| Material addition             | Steel          |