


Technical data sheet

Movable mounting lid for UZD350, nominal size 4

Item number: 7400506



Movable mounting lid for underfloor junction and branch boxes of type UZD350-4 for the installation or creation of an installation unit. Suitable for height-adjustable cassettes of nominal size 4. For later adaptation of the cassette position to the floor design, after the underfloor junction box has been mounted. Horizontal moving of the cassette by 17 mm in all directions possible (max. 34 mm), based on a centralised position. Possible rotation up to 7° .



St Steel

FS Strip galvanised

Master data

Item number	7400506
Type	DUG 350 V4
Description 1	Sliding mounting lid
Description 2	for UZD350 with RKN4
Manufacturer	OBO
Dimension	383x383x26
Material	Steel
Surface	Strip galvanised
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	495.82 kg
Weight unit	kg/100 pc.


Technical data sheet

Movable mounting lid for UZD350, nominal size 4

Item number: 7400506



Dimensions



Length	383 mm
Width	383 mm
Height	4 mm
Dimension a	234 mm
Dimension A	383 mm

Technical data

Mounting opening cover	no
Floor care	Dry
Seal installation option	no
Installation opening for on-floor tank	no
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	yes
Trunking width, max.	350 mm
Trunking width, min.	190 mm
Material thickness	4 mm
Mounting opening	Square
Nominal size	350 mm
Nominal size for device installation units	4
Heavy-duty version	no