

# Technical data sheet

## Metal strip clips, wide

Item number: 7203113



Metal strip clip in a smooth finish with ball lock. For high-temperature and weather-resistant fastening. Use spring chuck MBS-Z for tightening.

|    |                 |
|----|-----------------|
| A2 | Stainless steel |
| 2B | Bright, treated |

### Master data

|                     |                        |
|---------------------|------------------------|
| Item number         | 7203113                |
| Type                | MBS 120 A2             |
| Description 1       | Strip clip             |
| Manufacturer        | OBO                    |
| Dimension           | 12x1200                |
| Colour              | stainless steel        |
| Material            | Stainless steel 1.4301 |
| Surface             | Bright, treated        |
| Surface standard    |                        |
| Smallest sales unit | 25                     |
| Unit of quantity    | Piece                  |
| Weight              | 3 kg                   |
| Weight unit         | kg/100 pc.             |

### Dimensions

|             |          |
|-------------|----------|
| Length      | 1,200 mm |
| Width       | 12 mm    |
| Height      | 6.5 mm   |
| Dimension L | 1,200 mm |
| Dimension t | 0.25 mm  |

# Technical data sheet

## Metal strip clips, wide

Item number: 7203113



### Technical data

|                                   |                  |
|-----------------------------------|------------------|
| Version for                       | Without toothing |
| Strip closure                     | Ball lock        |
| Fastening type                    | Without          |
| Labelling area                    | Without          |
| Halogen-free                      | yes              |
| Releasable lock                   | no               |
| Max. Bundle diameter              | 175 mm           |
| MIL approval                      | no               |
| Mounting temperature, max.        | 50 °C            |
| Min. mounting temperature         | 5 °C             |
| Reflective                        | no               |
| ROHS-conformant                   | yes              |
| Permitted temperature range, max. | 70 °C            |
| Permitted temperature range, min. | -20 °C           |
| Transparent                       | no               |
| UL approval                       | no               |
| UV-resistant                      | yes              |
| VG approval                       | no               |