

Technical data sheet

Support profile for PV module mounting

Item number: 5900410



Support profile to mount photovoltaic modules on flat and pitched roofs. Flat roof mounting in combination with UniBase universal stand and STK and STL short and long supports. Lockable fastening of the profile on the stand with UniBase AMP adapter. Pitched roof mounting in combination with universal DHU roof hook. Lockable fastening of the profile on roof hooks. Screwable connection of multiple support profiles with LV 45 straight connectors and KV 45 cross-connectors. With 10 mm groove on both sides to accept slide nuts and universal and earthing clamps.



Alu	Aluminium
BK	Bright

Master data

Item number	5900410
Type	TP 45 4700 ALU
Description 1	Truss profile
Description 2	for flat/pitched roof system
Manufacturer	OBO
Dimension	40x45x4700
Colour	aluminium
Material	Aluminium
Surface	Bright
Surface standard	
Smallest sales unit	4
Unit of quantity	Piece
Weight	485.04 kg
Weight unit	kg/100 pc.


Technical data sheet

Support profile for PV module mounting

Item number: 5900410



Dimensions



Length	4,700 mm
Width	40 mm
Height	45 mm

Technical data

ROHS-conformant	yes
Cable duct, integrated	no
Cable duct optional	no
Section modulus Sx	3680 mm ³
Section modulus Sy	3760 mm ³